DUS 1717

DRAFT UGANDA STANDARD

First Edition 2017-mm-dd





Reference number DUS 1717: 2017

© UNBS 2017

Compliance with this standard does not, of itself confer immunity from legal obligations

A Uganda Standard does not purport to include all necessary provisions of a contract. Users are responsible for its correct application

© UNBS 2017

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilised in any form or by any means, electronic or mechanical, including photocopying and microfilm, without prior written permission from UNBS.

Requests for permission to reproduce this document should be addressed to

The Executive Director Uganda National Bureau of Standards P.O. Box 6329 Kampala Uganda Tel: +256 414 333 250/1/2/3 Fax: +256 414 286 123 E-mail: <u>info@unbs.go.ug</u> Web: www.unbs.go.ug

Contents

Page

Forewo	rd	iv
Introdu	ction	v
1	Scope	.1
2	Normative references	.1
3	Terms and definitions	.1
4 4.1 4.1.1 4.1.2 4.1.3	Types of baker's yeast Fresh Baker's Yeast (FBY) Block or Compressed baker's yeast Granulated (crumbled) baker's yeast Liquid baker's yeast	2222
4.2 4.2.1 4.2.2	Dry Baker's Yeast (DBY) Active dry yeast Instant dry yeast	2
5 5.1 5.2 5.2.1 5.2.2	Requirements General requirements Specific requirements Physicochemical requirements Microbial requirements	2333
6	Contaminants	3
7 7.1 7.2	Packaging Fresh Baker's Yeast Dry Baker's Yeast	3 3 4
8	Weights and Measures	4
9	Labelling	4
10	Sampling	4
Annex	A (normative) Determination of moisture	.5
Annex	B (normative) Test for dispersibility in water	6
Annex	C (normative) Determination of fermenting power	.7
Annex	D (normative) Determination of dough raising capacity1	0
Annex	E (normative) Determination of bacterial rope spore count1	1
Bibliog	raphy1	2

Foreword

Uganda National Bureau of Standards (UNBS) is a parastatal under the Ministry of Trade, Industry and Cooperatives established under Cap 327, of the Laws of Uganda, as amended. UNBS is mandated to co-ordinate the elaboration of standards and is

(a) a member of International Organisation for Standardisation (ISO) and

(b) a contact point for the WHO/FAO Codex Alimentarius Commission on Food Standards, and

(c) the National Enquiry Point on TBT Agreement of the World Trade Organisation (WTO).

The work of preparing Uganda Standards is carried out through Technical Committees. A Technical Committee is established to deliberate on standards in a given field or area and consists of key stakeholders including government, academia, consumer groups, private sector and other interested parties.

Draft Uganda Standards adopted by the Technical Committee are widely circulated to stakeholders and the general public for comments. The committee reviews the comments before recommending the draft standards for approval and declaration as Uganda Standards by the National Standards Council.

The technical committee responsible for this document is UNBS TC2 [*Technical Committee on Food and Agriculture standards*], Subcommittee SC6, [*Food Additives & Contaminants Subcommittee*].

Introduction

Strains of yeast, essential for regulating the fermentation and aromatic activity of fermented doughs are known as baker's yeast. These yeasts play three major roles; (i) increasing the volume of dough by producing carbon dioxide via alcoholic fermentation of sugars present in the dough, (ii) bringing about change in the structure and texture of the dough because of the carbon dioxide bubbles, and (iii), adding flavour to baked product.

In Uganda, different types of baker's yeast are available for both commercial bakeries and for home use. Most of these yeasts are imported.

This Draft Uganda Standard was developed to ensure the safety and quality of baker's yeast produced and/or traded in the country.

Baker's Yeast — Specification

1 Scope

This Draft Uganda Standard specifies the requirements and the methods of sampling and test for baker's yeast.

2 Normative references

The following referenced documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

US 45, General Standard for Food Additives

US 277, Labelling of food additives when sold as such — General requirements

US 738, General standard for contaminants and toxins in food and feed

US CAC/GL 50, General guidelines on sampling

US EAS 1, Wheat flour – Specification

US EAS 38, Labelling of pre-packaged foods - General requirements

US ISO 4832, Microbiology of food and animal feeding stuffs — Horizontal method for the enumeration of coliforms — Colony-count technique

US ISO 6579, Microbiology of food and animal feeding stuffs — Horizontal method for the detection of Salmonella spp.

US ISO 6888, Microbiology of food and animal feeding stuffs — Horizontal method for the enumeration of coagulase-positive staphylococci (Staphylococcus aureus and other species)

US ISO 7251, Microbiology of food and animal feeding stuffs — Horizontal method for the detection and enumeration of presumptive Escherichia coli — Most probable number technique

The Weights and Measures (Sales and Labelling of goods) Rules, 2007

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

baker's yeast

cells of one or more strains of the fungus *Saccharomyces cerevisiae* that aid the fermentation and aromatic activity of fermented doughs.

3.2

food grade material

a material, made of substances that are safe and suitable for their intended use and which will not impart any toxic substance or undesirable odour or flavour to the product.

4 Types of baker's yeast

Baker's yeast shall be categorised in two types; Fresh Baker's Yeast and Dry Baker's Yeast.

4.1 Fresh Baker's Yeast (FBY)

Fresh Baker's yeast shall consist of living cells of *Saccharomyces cerevisiae*. It shall be ivory in colour, with an odour typical of yeast and free of extraneous materials. It shall not be slimy or mouldy and shall not show any signs of deterioration or decomposition.

Fresh baker's yeast shall be in three major forms; block or compressed yeast, granulated yeast or liquid yeast.

4.1.1 Block or compressed baker's yeast

This shall be in the form of a block. The texture or consistency shall be either high plasticity (kneadable, deformation possible without breakage) or friable/crumbly (blocks easily broken into small pieces). Edible starch may be added in a quantity not exceeding 7 percent by mass on dry basis. Permissible edible binders and fillers may be added in accordance to US 45.

4.1.2 Granulated (crumbled) baker's yeast

This shall be in the form of small granules.

4.1.3 Liquid baker's yeast

This shall be a liquid suspension of yeast cells in water with a cream-like viscosity.

4.2 Dry Baker's Yeast (DBY)

Dry baker's yeast shall consist of living but inactive cells of *Saccharomyces cerevisiae*. It shall be in the form of powder, small granules, pellets or flakes, dried to a low moisture content that stops the yeasts' metabolic activity. It shall be ivory in colour, with an odour characteristic of yeast and free from adulterants and other extraneous materials. It shall not be mouldy and shall not show any sign of deterioration or decomposition. Edible starch may be added in a quantity not exceeding 10 percent by mass of the product.

Dry baker's yeast shall be in two forms; either active dry yeast or instant dry yeast.

4.2.1 Active dry yeast

This is yeast that requires reactivation by rehydration using warm water between 38–45 °C prior to use. It shall be of spheroid particles, 0.2–3 mm in diameter.

4.2.2 Instant dry yeast

This is yeast dried in a such a way that rehydration is not necessary to facilitate reactivation. It shall consist of porous cylindrical yeast particles with an approximate diameter of 0.5 mm and length up to a few millimetres.

5 Requirements

5.1 General requirements

Baker's yeast shall be manufactured, packaged and stored under hygienic conditions in certified premises. Its distribution shall be under hygienic conditions. Bacteriologically free air filters shall be used for filtering the air required to aerate the fermenters.

5.2 Specific requirements

5.2.1 Physicochemical requirements

Baker's yeast, when tested in accordance with the specified methods shall conform to the physicochemical parameters specified in table 1.

		Requirer	nents for	Mathedations	
S/N	Parameter	FBY	DBY	Method of test	
i	Moisture, percent by mass, Max.	73	8	Annex A	
ii	Dispersibility in water	No yeast cell deposits	No yeast cell deposits	Annex B	
iii	Fermenting power, Min.	1000	350	Annex C	
iv	Dough-rising capacity	To satisfy the test	To satisfy the test	Annex D	

Table 1 — Physicochemical requirements for Baker's Yeast

5.2.2 Microbial requirements

When tested in accordance with the specified methods, baker's yeast shall conform to the microbial limits indicated in Table 2.

		Requirer	nents for	
S/N	Parameter	FBY	DBY	Method of test
v	Coliform count (CFU/g), Max.	10	00	US ISO 4832
vi	Escherichia coli (MPN/g), Max.	100	10	US ISO 7251
vii	Salmonella (CFU/25 g)	Absent		US ISO 6579
viii	Staphylococcus aureus (CFU/g), Max.	10		US ISO 6888
ix	Rope spore count (CFU/g), Max.	10	100	Annex E

Table 2 — Microbial requirements for Baker's Yeast

6 Contaminants

The products shall comply with the contaminant limits cited in US 738.

7 Packaging

7.1 Fresh Baker's Yeast

Compressed and granulated baker's yeast shall be packaged in clean waxed paper or any other suitable food grade wrapping material or non-toxic wrappers to preserve its freshness and to prevent undue deterioration during storage and distribution. Liquid baker's yeast shall be packed in containers suitable for liquid food stuffs.

7.2 Dry Baker's Yeast

Dry baker's yeast shall be packaged in clean, sound, air-tight food grade containers, preferably tin containers in such a manner as to prevent the absorption of moisture and to prevent undue deterioration during storage and distribution.

8 Weights and Measures

The weight of the packages shall comply with the Weights and Measures (Sales and Labelling of goods) Rules.

9 Labelling

In addition to the labelling requirements of US 277, the packages shall be legibly and indelibly marked with the following information:

- a) Name and type of the product. For example, "Baker's Yeast, Granulated", "Instant Baker's Yeast", "Granulated Baker's Yeast",
- b) Name and physical address of the manufacturer/distributor,
- c) Date of manufacture
- d) Best before date
- e) Net weight of the product in metric units,
- f) The list of additives in descending order by quantity when used,
- g) Declaration 'Contains edible starch', when edible starch is added
- h) Instructions for storage, and,
- i) Instructions of use

10 Sampling

Representative samples for the products shall be drawn in accordance with US CAC/GL 50.

Annex A

(normative)

Determination of moisture

A1 Apparatus

- Dish With a cover, made of glass or aluminium; about 25 mm in diameter
- Glass stirring Approximately 60 mm long, with a flattened end.

A-2 Reagent

- Ethyl alcohol or rectified spirit.

A-3 Procedure

Weigh the dish with the cover and stirring rod. Transfer to this, about 10 g of dry yeast or 2.5 g of fresh yeast and weigh accurately to the nearest milligram.

Remove the cover of the dish and add 5 ml of alcohol. Mix thoroughly using the stirring rod and leave the stirring rod in the weighing dish. Dry at 105 ± 1 °C for 4 hours for fresh baker's yeast and 6 hours for dry baker's yeast. Cool the dish in a desiccator and weigh

A-4 Calculation

The moisture, percent by mass = $\frac{100 \times (M_1 - M_2)}{M_1 - M_2}$

where,

M = mass, in grams of the dish, its cover and the stirring rod;

 M_1 = mass, in grams of the dish, its cover and the stirring rod with the sample before drying, and,

 M_2 = mass, in grams of the dish, its cover and the stirring rod with the sample after drying.

Annex B

(normative)

Test for dispersibility in water

B-1 Procedure

Weigh 5 g of dry baker's yeast or 20 g of fresh baker's yeast into a 400 ml beaker and add 50 ml of distilled water at 40 °C. Leave the product undisturbed for 5 minutes and thereafter, stir for 2 minutes. Take into a one litre graduated cylinder, 900 ml of distilled water at 40 °C in the case of dry baker's yeast and at 30 °C for fresh baker's yeast. Pour the slurry from the beaker into the water in the graduated cylinder. Wash the beaker with 50 ml of distilled water, pour it into the cylinder and leave it undisturbed for 5 minutes. Check for any deposits at the bottom of the cylinder. If no deposits appear at the bottom of the cylinder, the material shall be considered to have passed the test.

Note - If starch was added to the yeast, it may form a sediment which may contain a few yeast cells.

Annex C

(normative)

Determination of fermenting power

C-1.Apparatus

- Fermentometer

The assembly of the apparatus is illustrated in Fig. 1. It consists of a 250 ml flat-bottomed flask (A), whose mouth is fitted with a ground-glass joint having a glass delivery tube bent at right angle. It is connected to a three-way T-shaped stop-cock (B) which in turn is fitted on a 100 ml graduated tube (D) of the manometer. (E) is the manometer reservoir of 250 ml capacity. I is the iron stand. D and E are connected by a PVC tube F. G is a water bath.

- Barometer
- Thermometer

C-2 Reagents

- Sugar phosphate mixture Grind and mix thoroughly 400 g of sucrose, 25 g of diammonium hydrogen phosphate [(NH₄)2 HPO₄] and 25 g of dipotassium hydrogen phosphate (K₂HPO₄).
- Calcium sulphate solution Dilute 30 g of saturated calcium sulphate solution (CaSO₄ .2H₂0) with 70 g of distilled water.
- Manometer solution Weigh 200 g of anhydrous calcium chloride and 10 g of cupric chloride and dissolve in distilled water. Add a little hydrochloric acid so that the final pH after making up the solution to 2 litres does not exceed 5.0.

C-3 Procedure

Mix 6.75 g of the sugar phosphate mixture with 75 ml of the calcium sulphate solution in the flask. Add to it, 3.67 g of fresh baker's yeast or 0.893 g of dry baker's yeast. Stir well to disperse the yeast. Keep the flask in the water-bath at 30 °C throughout the experiment. Bring the three-way T-shaped stop-cock of the manometer into a position which allows displacement of initial air (by the carbon dioxide evolved) to escape to the atmosphere without displacement of the manometer fluid. This displacement is allowed for the first 13 minutes after which the stop-cock position is altered to allow the carbon dioxide evolved to enter the manometer and bring about the displacement of the manometer fluid. Shake the contents of the flask every 10 minutes.

While taking the reading of the gas evolved, the level of the fluid in the manometer shall be adjusted by sliding the reservoir arm of the manometer and the volume of gas evolved at this pressure (which will now be equal to the atmospheric pressure) shall be recorded.

As soon as the reading is taken, the initial gas formed which has just been measured, is allowed to escape into the atmosphere by operating the three-way stop-cock and the stop-cock position is again adjusted to take the second reading. For fresh baker's yeast, readings should be taken every 10 minutes and for dry baker's yeast, readings shall be taken every 30 minutes. In both the cases, readings shall be taken for 3 hours,

The room temperature and the atmospheric pressure shall also be noted during the course of the experiment. The readings are recorded in a tabulated form (see Table 2) and the total volume of gas produced is calculated and corrected at 101 kPa pressure and 20 °C temperature by the formula given under C-4.



 Table 2 Recording Carbon dioxide evolved every 10/30 minutes

Time	Volume of CO ₂ evolved	Room temperature	Atmospheric pressure	Corrected volume
	(ml)	(°C)	(mmHg)	(ml)
08:00				
08:10				
08:20				
08:30				
11:00				

C-4. Calculations

Fermenting power (corrected volume in ml) = $\frac{Observedvolumex Observedaverage pressurex 293}{760 \times (273 + Average room temperatue)}$

The mass of carbon dioxide evolved may be calculated from this corrected volume as

Mass of carbon dioxide evolved = $\frac{44 \times V}{22400}$ g, where V is the corrected volume of carbon dioxide evolved.

Annex D

(normative)

Determination of dough raising capacity

D-1. Materials

- Wheat flour conforming to US EAS 1
- Sucrose

D-2. Procedure

Mix 4.0 g of fresh baker's yeast or 1.0 g of dry baker's yeast with 100 g of wheat flour. Add 1.0 to 1.5 g of sucrose and a suitable quantity of water (about 55 ml). Knead well. Press the resulting dough into a glass beaker. Note the level of the dough by means of a scale, from the bottom of the beaker. Keep it covered for one hour at 27 °C. At the end of this period, note the level again.

The product shall be deemed to have satisfied the test if the rise in level is at least 80 percent of the original for dry baker's yeast and 110 percent for fresh baker's yeast.

Annex E

(normative)

Determination of bacterial rope spore count

F-1 Reagents

- Sterilised peptone water 0.1 percent.
- Tryptone glucose extract (TGE) Agar
 - Tryptone 5.0 g
 - Yeast extract 2.5 g
 - Sodium chloride 6.5 g
 - Final pH = 7.0 ± 0.1
- Agar, bacteriological grade (see Note) 15.0 g
- Distilled water 1 litre
- Glucose (dextrose) 1.0 g

Note - Granulated or chopped shreds, practically free from thermophilic bacteria shall be used.

F-2 Procedure

Weigh 22 g of wheat flour in a suitable sanitised container and transfer to a conical flask containing 100 ml of sterile 0.1% peptone water and sterile sand or glass beads. Blend on a shaker for about two minutes. Dilute the blended mixture further; 1:10, 1:100, 1:1000, 1:10000, etc., by dilution technique, using sterile peptone water.

Prepare tryptone glucose extract (TGE) agar; 100 ml per 250 ml conical flask. Prepare one additional flask of medium to serve as sterility control. Sterilise at 121 °C for 15 minutes and then cool to 45 °C in a water-bath. Pipette volumes of the blended mixture into a series of TGE agar flasks while they are held in the water-bath; 10 ml into the first, 1 ml into the second and 1 ml of each dilution into the third, fourth and fifth TGE flask and so on. Gently agitate the flasks to disperse the blended mixture throughout the medium.

Transfer the flasks without delay to a water-bath adjusted to 65 °C to 90 °C and hold for 30 minutes with gentle shaking occasionally to assist heat distribution. After 30 minutes of heat treatment, cool the flasks to about 45 °C without allowing the agar to gelatinise. Pour 100 ml of the medium into each flask representing the product and sterility control into a set of 5 sterile petri dishes in approximately equal volumes of about 20 ml per plate. When agar has solidified, invert the plates and incubate at 35 °C for 48 hours.

Count the surface and sub-surface colonies. The sum of the colonies on the set of 5 plates poured from TGE agar, containing 10 ml of the blended mixture represents the number of aerobic and mesophilic spores per gram of the product. Similarly, 1 ml of the blended and 1 ml of each dilution are equal to 0.01, 0.001, 0.0001 and 0.00001 of the number of spores per gram and shall be multiplied by the respective dilution factor.

Generally, the set of plates showing about 30–60 colonies per plate are to be chosen for the counting purposes.

F-3. Precautions and Limitations

The procedure permits enumeration of aerobic and mesophilic spores in food samples containing relatively higher number of spores by higher dilution of the samples prior to heat treatment.

Certain thermophilic strains may also be indicated in this method in which case a separate enumeration method for thermophiles may be adopted and their numbers subtracted from the spore count.

Bibliography

- [1] COFALEC (2012): General characteristics of dry baker's yeast
- [2] COFALEC (2012): General characteristics of fresh baker's yeast
- [3] IS 1320 (1988) (Third Edition) Specification for baker's yeast (Reaffirmed in 2010)

Certification marking

Products that conform to Uganda standards may be marked with Uganda National Bureau of Standards (UNBS) Certification Mark shown in the figure below.

The use of the UNBS Certification Mark is governed by the Standards Act, and the Regulations made thereunder. This mark can be used only by those licensed under the certification mark scheme operated by the Uganda National Bureau of Standards and in conjunction with the relevant Uganda Standard. The presence of this mark on a product or in relation to a product is an assurance that the goods comply with the requirements of that standard under a system of supervision, control and testing in accordance with the certification mark scheme of the Uganda National Bureau of Standards. UNBS marked products are continually checked by UNBS for conformity to that standard.

Further particulars of the terms and conditions of licensing may be obtained from the Director, Uganda National Bureau of Standards.

ICS 67.220.20

Price based on nn pages