DRAFT UGANDA STANDARD

Second Edition 2018-mm-dd

Lipstick — Specification



Reference number DUS 875: 2018

DUS 875: 2018

Compliance with this standard does not, of itself confer immunity from legal obligations

A Uganda Standard does not purport to include all necessary provisions of a contract. Users are responsible for its correct application

© UNBS 2018

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilised in any form or by any means, electronic or mechanical, including photocopying and microfilm, without prior written permission from UNBS.

Requests for permission to reproduce this document should be addressed to

The Executive Director
Uganda National Bureau of Standards
P.O. Box 6329
Kampala
Uganda

Tel: +256 414 333 250/1/2/3 Fax: +256 414 286 123 E-mail: info@unbs.go.ug Web: www.unbs.go.ug

Foreword

Uganda National Bureau of Standards (UNBS) is a parastatal under the Ministry of Trade, Industry and Cooperatives established under Cap 327, of the Laws of Uganda, as amended. UNBS is mandated to coordinate the elaboration of standards and is

- (a) a member of International Organisation for Standardisation (ISO) and
- (b) a contact point for the WHO/FAO Codex Alimentarius Commission on Food Standards, and
- (c) the National Enquiry Point on TBT Agreement of the World Trade Organisation (WTO).

The work of preparing Uganda Standards is carried out through Technical Committees. A Technical Committee is established to deliberate on standards in a given field or area and consists of key stakeholders including government, academia, consumer groups, private sector and other interested parties.

Draft Uganda Standards adopted by the Technical Committee are widely circulated to stakeholders and the general public for comments. The committee reviews the comments before recommending the draft standards for approval and declaration as Uganda Standards by the National Standards Council.

The committee responsible for this document is Technical Committee UNBS/TC 5, Chemicals and Environment, Subcommittee SC 1, *Industrial and Public Health chemicals*.

This second edition cancels and replaces the first edition (US 875:2009), which has been technically revised.

Lipstick — Specification

1 Scope

This Draft Uganda Standard specifies the requirements, sampling and methods of test for lipstick.

2 Normative references

The following referenced documents referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EAS 847-16, Oils for cosmetic industry — Methods of test — Part 16: Determination of Heavy metal Content

EAS 847-18, Cosmetics — Analytical methods — Part 18: Determination of thermal stability

US ISO 24153, Random sampling and randomisation procedures

WDUS ISO 21149, Cosmetics -- Microbiology -- Enumeration and detection of aerobic mesophilic bacteria

US EAS 346, Labelling of cosmetics — General requirements

US EAS 377 (all parts), Cosmetics and cosmetic products

US ISO 3960, Animal and vegetable fats and oils — Determination of peroxide value — Iodometric (visual) endpoint determination

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EAS 846 and the following apply ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at http://www.iso.org/obp

Lipstick

cosmetic product containing pigments, oils, waxes, and emollients that apply color, texture, and protection to the lips

4 General requirement

- 4.1 The lipstick shall be firm but not brittle in texture. It shall have an attractive appearance, pleasant taste and feel on the lips. It shall be reasonably free from sweating, bloom and rancidity.
- 4.2 All ingredients used including dyes, pigment and colours shall conform to US EAS 377(all Parts) Cosmetics and cosmetic products

5 Quality requirements

The lipstick shall also comply with the requirements specified in Table1.

Table 1 — Quality requirements for lipstick

Characteristic	Requirement	Method of test
Softening point, °C	55	Annex A
Melting point, ° C	55-65	EAS 847-6
Thermal Stability	To pass test	EAS 847-18
Microbiological examination	Not more than 100 micro-organisms per gram	WDUS ISO 21149
Peroxide number, max.	10	US ISO 3960
Breaking load value, min.	200	Annex B
Particle size of undispersed pigments microns, max	40	Annex C
Arsenic (As ₂ O ₃) mg/l, max.	2	EAS 847-16
Mercury (Hg) mg/l, max	2	EAS 847-16
Heavy metals (Pb) mg/l, max.	10	EAS 847-16

Note- The total amount of heavy metals as lead, mercury and arsenic, in combination in the finished product shall not exceed 10 ppm

6 Packaging

Each lipstick shall be packed in suitable containers which shall not interact chemically with the lipstick and shall be strong enough to prevent contamination of lipstick adequately during normal handling, transportation and storage

7 Labelling

In addition to the labelling requirements in US EAS 346, the package shall be legibly and indelibly marked with the following information:

- a) manufacturer's name and physical address;
- b) product name "lipstick";
- c) batch number;
- d) Shade number or shade name;
- e) country of origin;
- f) month and year of manufacture and expiry, and
- g) recommended storage conditions

8 Sampling

Sampling shall be carried in accordance with US ISO 24153.

DUS 875: 2018

Annex A (normative)

Softening point

A.1 Apparatus

- A.1.1 Flat bottom tube, 12 cm long and 2.5 cm in diameter
- A.1.2 Thermometer, accurate to 0.1 °C

A.2 Procedure

- A.2.1 Place the lipstick with protruded salve in the flat bottom tube.
- A.2.2 Fix the thermometer through a cork in such a way that the bulb of the thermometer just touches the lipstick salve.
- A.2.3 Insert this arrangement into a 1-litre beaker filled with water to a level one centimetre above the upper tip of the lipstick salve.
- A.2.4 Slowly heat the water while stirring so that temperature rises at a rate not exceeding 2 °C per min.
- A.2.5 When the temperature reaches about 45 °C, raise the temperature at the rate of 1 °C per min constantly watch the lipstick salve. Record the temperature when the salve starts bending and losing its shape.

Annex B

(normative)

Breaking load test

B.1 General

This test gives the value of maximum load a lipstick can withstand before" it breaks.

B.2 Apparatus

- B.2.1 Burette, 500 mL capacity
- B.2.2 Screw chuck, to hold the lipstick
- B.2.3 Aluminium cup, of 6 cm diameter and 12 cm length with an arrangement of a hook to suspend it on lipstick salve

B.3 Procedure

- B.3.1 Fix firmly the lipstick container with protruded salve of diameter ranging 11 mm to 13 mm, into a screw type of chuck so that the assembly is perfectly horizontal.
- B.3.2 Adjust the burette just above the lipstick salve. Make a marking at a distance of 1.5 cm from the base of the salve where the lipstick salve sits in salve holder cup.
- B.3.3 Weigh the aluminium container along with hook and suspend it on this 1.5 cm mark slowly release water from the burette into the aluminium container till the salve breaks. Burette reading added with the mass of the suspended container gives the breaking load of the lipstick.

Annex C

(normative)

Particle size of undispersed pigments

C.1 Apparatus

- C.1.1 Microscope
- C.1.2 Glass slides

C.2 Procedure

- C.2.1 Apply a small portion of the lipstick paste on glass slide. Press and spread it with the help of another glass slide. Separate both the glass slides.
- C.2.2 Observe one of the slides under microscope using a specially calibrated eye piece. Determine the particle size of the largest pigment particle.

Bibliography

- [1] ASTM D1321 10, Standard Test Method for Needle Penetration of Petroleum Waxes
- [2] US 875:2009, Lipstick Specification

Certification marking

Products that conform to Uganda standards may be marked with Uganda National Bureau of Standards (UNBS) Certification Mark shown in the figure below.

The use of the UNBS Certification Mark is governed by the Standards Act, and the Regulations made thereunder. This mark can be used only by those licensed under the certification mark scheme operated by the Uganda National Bureau of Standards and in conjunction with the relevant Uganda Standard. The presence of this mark on a product or in relation to a product is an assurance that the goods comply with the requirements of that standard under a system of supervision, control and testing in accordance with the certification mark scheme of the Uganda National Bureau of Standards. UNBS marked products are continually checked by UNBS for conformity to that standard.

Further particulars of the terms and conditions of licensing may be obtained from the Director, Uganda National Bureau of Standards.





ICS 71.100.70

Price based on nn pages